



# CLEARSEAL

## ELASTOMERIC WATERPROOF COATING SYSTEM

### PRODUCT DESCRIPTION

One pack acrylic copolymer composition having excellent water resistance, weathering resistance, extra ordinary adhesiveness, fast drying, flexible film with breathing properties.

### RECOMMENDED USES

Excellent composition for exterior coatings on Walls and Roofs to stop water ingress. When applied on external walls it provides a tough watertight barrier and also decorative appeal. When applied on roof the coating should be protected from mechanical damage and wear and tear. Reinforcement with synthetic fibre mesh is recommended where movement in substrata is expected.

### SURFACE PREPARATION

Cement concrete surface should be free of dust and loose particles. It should be thoroughly abraded by a wire brush and loosened particles should be removed by washing or blown air. The surface should be free of any oil or grease. It can be applied on damp and moist surface also. It is used as a protective coating on Sprayed Polyurethane foam on roofs.

### PRODUCT SPECIFICATIONS

Method of Application	Brush or spray
Drying Time	20 min. (surface dry), 2hrs. (hard dry)
Recoating Interval	4 hrs. (min.)
No. of Coats Recommended	2(min.)
Expected Film Life	10 Years if properly protected from mechanical damage.
Film Cure	7 days
Flexibility	Meets IS 101 specifications.
Covering Capacity	4-5sq.mtr/kg.(depending on porosity of surface) per coat.
Surface Finish	Smooth lustrous
Shades Offered	All standard shades

### SPECIAL INSTRUCTION

Stir the contents of drum containing base thoroughly to disperse settled matter.

### METHOD OF APPLICATION

1. Dilute **CLEARSEAL** with water in the ratio 1:2. Apply it as a primer coat by brush application.
2. Apply first coat of **CLEARSEAL** on the primed surface.
3. Apply second coat with inter coat interval of minimum 4 hrs.

*The manufacturer reserves the right to change the specifications. Apurva India Limited products are guaranteed against material manufacture and are sold subject to the company's Terms and Conditions of Sale. Whilst we endeavour to ensure that advice, specifications, recommendations and information given is correct, we can not have control over how our products are applied and will not accept liability, directly or indirectly, arising from application of our materials.*

For further details please contact :

### APURVA INDIA LIMITED

(FORMERLY APURVA BUILDCARE TECHNOLOGIES P LIMITED)  
New Udyog Mandir No.2, 2<sup>nd</sup> Floor, Office No.2,  
7C, Pitambar Lane, Mahim(w), Mumbai 400 016  
Tel.No. 91 22 24475051/52/53/54/55, Fax No. 91 22 24475056  
E-Mail: [info@apurvaindia.in](mailto:info@apurvaindia.in) Website: [www.apurvaindia.in](http://www.apurvaindia.in)





