

DURASEAL

ACRYLIC WEATHERPROOFING COATING

PRODUCT DESCRIPTION

High performance acrylic latex based weatherproofing and decorative coating for building exteriors. It offers long term protection and retention of good aesthetics due to excellent UV and fungus resistance.

PRODUCT ATTRIBUTES

- * It forms a smooth and durable film
- * Fungus Control - Due to incorporation of highly effective broad spectrum fungicide, it offers long term protection against fungal growth.
- * UV Resistance - It is completely resistant to UV radiation.
- * Excellent Breathability - Coating is permeable to water vapour.
- * No chalking and peeling.

PRODUCT SPECIFICATIONS

Form	Pasty liquid
Method of Application	Brush, roller or Spray
Drying Time	30 minutes (surface dry) 2 hours (hard dry) (Depends on Relative Humidity and Temperature)
Recoating Interval	4 hours (minimum)
Number of Coats	2 coats (minimum)
Recommended Covering Capacity	5 to 6 m ² /kg for 2 coats depending on surface porosity and roughness over the primed surface.
Fungus Resistance	Resistant to fungus
Colour Shades	All standard shades
Shelf Life	Minimum 6 months if sealed drum is not opened

METHOD OF APPLICATION

a) **SURFACE PREPARATION**

The concrete or plastered surface should be washed and cleaned to remove dust, dirt, old paint, if any and laitence. The surface should be minimum 28 days old. All column or beam and wall joints should be checked thoroughly and sealed. All cracks above 1mm width should be properly sealed with non shrink grouts or sealents. The surface should be free of any oil and grease .

b) **PRIMER COAT**

Apply a coat of **CEMENT** paint as a priming coat on clean concrete or plastered surface with brush application for proper sealing and bonding.

c) **TOP COATS**

Add water (upto 30%) to **DURASEAL** to obtain proper consistency for brushing. Apply first coat on primed surface by brush or roller. Apply second coat after minimum interval of 4 hours.

SPECIAL INSTRUCTIONS

- * Stir the contents of the drum thoroughly to disperse the settled matter.
- * Do not store the drums in direct sunlight.

The manufacturer reserves the right to change the specifications. Apurva India Limited products are guaranteed against material manufacture and are sold subject to the company's Terms and Conditions of Sale. Whilst we endeavour to ensure that advice, specifications, recommendations and information given is correct, we can not have control over how our products are applied and will not accept liability, directly or indirectly, arising from application of our materials.

For further details please contact :

APURVA INDIA LIMITED

(FORMERLY APURVA BUILD CARE TECHNOLOGIES P LIMITED)

New Udyog Mandir No.2, 2nd Floor, Office No.2,
7C, Pitambar Lane, Mahim(w), Mumbai 400 016

Tel.No. 91 22 24475051/52/53/54/55, Fax No. 91 22 24475056

E.Mail: info@apurvaindia.in Website: www.apurvaindia.in



