



DURASEAL

ACRYLIC WEATHERPROOFING COATING

PRODUCT DESCRIPTION

High performance acrylic latex based weatherproofing and decorative coating for building exteriors. It offers long term protection and retention of good aesthetics due to excellent UV and fungus resistance.

GREEN BUILDING COMPLIANCE

This product has following distinct advantages:

- Water-based Wall Coatings which conform to the Indian Green Building Council (IGBC) limits of permissible Volatile Organic Content (VOC).
- Hygienic and environment friendly
- Easily cleanable
- Antifungal
- Antimicrobial
- Non Smelling
- Low maintenance
- Free of allergens and without carcinogens, it is one of the most eco-friendly exterior wall coatings.
- This paint acts like an insulator for the exterior wall providing long lasting protection against UV degradation and atmospheric pollution.
- LEED compliant
- Ideal for use in Green Building

PRODUCT ADVANTAGES

- It forms a smooth and durable film
- Fungus Control - Due to incorporation of highly effective broad spectrum of fungicide, it offers long term protection against fungal growth.
- UV Resistance - It is completely resistant to UV radiation.
- Excellent Breathability - Coating is permeable to water vapour.
- No chalking and peeling.

APPLICATION AREAS

Excellent composition for exterior wall coatings.

PRODUCT SPECIFICATIONS

Method of Application: Brush/Roller/Spray

Drying Time:

Surface Dry 20-30 minutes

Hard dry 2-3 hours

Recoating Interval: 4 hours minimum

No. of coats recommended: 2 coats

Coverage : 5 to 6 m²/kg for 2 coats depending on surface porosity and roughness over the primed surface.

Fungus Resistance: Resistant to fungus growth

Surface Finish : Smooth sheen

Shades Offered: All standard shades

Packing size 25kgs. 5 kgs.

SURFACE PREPARATION

The concrete or plastered surface should be washed and cleaned to remove dust, dirt, old paint, if any and laitence. The surface should be minimum 28 days old. All column or beam and wall joints should be checked thoroughly and sealed. All cracks above 1mm width should be properly sealed with non shrink grouts or sealants. The surface should be free of any oil and grease .

a) PRIMER COAT

Apply a coat of **CEMENT** paint as a priming coat on clean concrete or plastered surface with brush application for proper sealing and bonding.

b) TOP COAT

Add water (upto 30%) to **DURASEAL** to obtain proper consistency for brushing. Apply first coat on primed surface by brush or roller. Apply second coat after minimum interval of 4 hours.

SHELF LIFE

CLARESEAL has a shelf life of 6 months if kept in warehouse conditions at 30°C in the original, unopened pack.

STORAGE CONDITIONS

Store in dry conditions between 5°C and 30°C, away from sources of heat and naked flames, in the original, unopened packs. If stored at high temperatures the shelf life will be reduced.

SPECIAL INSTRUCTIONS

- Stir the contents of the drum thoroughly to disperse the settled matter.
- Do not store the drums in direct sunlight.

APURVA INDIA LIMITED

New Udyog Mandir No. 2, Office No. 2, 2nd floor, 7-C, Pitambar Lane, Mahim (W), Mumbai - 400 016, India.

Tel.: 91-22-24475051 | Fax: 91-22-24475056 | Website: www.apurvaindia.in





HANDLING & SAFETY

Keep the containers tightly sealed when not in use. Avoid skin contact and inhalation of fumes (if any). While spraying it is advised to wear a mask. If it comes in contact with the body, wash affected parts with plenty of water. In case of persistent irritation, contact a physician. It is advised that the workmen should use protectives like gloves, goggles etc

Disclaimer: *The manufacturer reserves the right to change the specifications. Apurva India Limited products are guaranteed against material manufactured and are sold subject to the company's Terms and Conditions of Sale. Whilst we endeavour to ensure that advice, specifications, recommendations and information given is correct, we cannot have control over how our products are applied and will not accept liability, directly or indirectly, arising from application of our materials.*

APURVA INDIA LIMITED

New Udyog Mandir No. 2, Office No. 2, 2nd floor, 7-C, Pitambar Lane, Mahim (W), Mumbai - 400 016, India.
Tel.: 91-22-24475051 | Fax: 91-22-24475056 | Website: www.apurvaindia.in

