



# WALGARD-WBA

## FUNGUS RESISTANT INTERIOR WALL FINISH

---

### **PRODUCT DESCRIPTION :**

One pack waterborne acrylic based interior wall finish designed to provide rich, lustrous and smooth film to provide hygienic surface.

### **PRODUCT ADVANTAGES**

Non smelling

It forms a very smooth film.

Forms a continuous flexible film with excellent crack bridging properties.

Fungus and Bacteria Control - Due to incorporation of broad spectrum fungicide it does not allow any fungal growth.

Good stain resistance.

Non Yellowing.

Easy to clean

Good resistance to water and cleaning chemicals.

As it is waterborne it is environment and user friendly.

### **RECOMMENDED USE**

Less Critical areas of Pharma Industry and Hospitals.

Electronics assembly and Computer Rooms.

Hotels and Flight Kitchens.

Dairies and Breweries.

Food and Meat Processing Plants.

Residential Premises

Public Places

### **PRODUCT SPECIFICATIONS**

Method of Application.....	Roller or Spray
Drying Time.....	1 hr.(surface Dry) /3 hrs. (Hard Dry)
Recoating interval.....	8 hrs. (Min.)
No. of coats recommended.....	2 min.
Surface finish.....	Satin
Covering Capacity.....	9-10 sq.mtr. / kg. per 2 coats depending on porosity, roughness and the material of substrate and also method of application.
Dry Film Thickness.....	75-85 $\mu$ at the above spread rate
Solid Content.....	60 $\pm$ 2% w/w
Shelf life.....	Minimum 6 months if sealed drum is not opened.
Fungus Resistance.....	Fully resistant to fungus growth
Colour Shades.....	White and pastel shades
Packing Size.....	5, 10, 20, 35 kg.

### **SURFACE PREPARATION**

The concrete surface should be thoroughly cleaned to remove all loose particles laitence and old paint, if any. Ensure that wall is protected from ingress of moisture from other side. The surface should be smoothed properly using suitable leveling putty to ensure hard and smooth surface. Sand the levelled surface using fine emery paper to smoothness.

P.T.O.

## **APPLICATION OF COATING**

Apply one coat of primer by diluting **WALGARD-WBA** with water in the ratio of 1:2. Apply first coat of **WALGARD-WBA** by adding upto 50% water. The second coat at the interval of 2-6 hours by adding upto 40% of water.

## **HANDLING & SAFETY**

1. Stir the contents of drum thoroughly to disperse the settled matter before use.
2. Ensure that areas where coating work is being carried out are properly ventilated.
3. It is advised that the workmen should use protectives like gloves, goggles etc..

*The manufacturer reserves the right to change the specifications. Apurva India Limited products are guaranteed against material manufacture and are sold subject to the company's Terms and Conditions of Sale. Whilst we endeavour to ensure that advice, specifications, recommendations and information given is correct, we can not have control over how our products are applied and will not accept liability, directly or indirectly, arising from application of our materials.*

*Apurva's wide range of quality products meets the tough requirements of the building industry. Constant interaction with clients, regular improvisation to meet growing needs and a strong commitment to provide products that perform has made Apurva a truly trusted name in the field.*

---

For further details please contact :

### **APURVA INDIA LIMITED**

(FORMERLY APURVA BUILD CARE TECHNOLOGIES P LIMITED)

New Udyog Mandir No.2, 2<sup>nd</sup> Floor, Office No.2,

7C, Pitambar Lane, Mahim(w), Mumbai 400 016

Tel.No. 91 22 24475051/52/53/54/55, Fax No. 91 22 24475056

E.Mail: [info@apurvaindia.in](mailto:info@apurvaindia.in) Website: [www.apurvaindia.in](http://www.apurvaindia.in)

---



