



WALKOTE

SKIM SMOOTH RENDERING PASTE

PRODUCT DESCRIPTION

Walkote is a specially formulated **water resistant** white cement based putty suitable for plastered and concrete surfaces for both internal and external walls.

Walkote superior formulation is designed to provide a smooth durable finish with excellent adhesion strength. The surface can be either brushed or trowelled finished to meet stringent requirements. Walkote yields a homogeneous paste that gives good workability on both vertical and overhead surfaces.

PRODUCT ADVANTAGES

- Premixed to ensure good consistent quality.
- Adjustable consistency & Excellent trowelability on application.
- Due to presence of cement and polymer, it provides a hard and tough surface.
- Being Cementitious it forms an excellent bond with plaster
- Seal all cracks and pores in the concrete
- Can be applied on moist plaster without waiting for drop in moisture. Hence improvement in Project Completion Schedule.
- Perfectly smooth finish.
- Compatible with decorative wall coatings.
- Water resistant and no curing required

METHOD OF APPLICATION

a) SURFACE PREPARATION

The surface must be clean, sound, dust-free, and without any traces of oil, laitance, paint or curing compound.

b) PRODUCT PREPARATION

Add approximately 9-10 litre of water to 25 kg of **Walkote**. Mix thoroughly for 3-5 minutes until the desired homogeneous paste is achieved and ready to use.

c) PRODUCT APPLICATION

Walkote is applied using a steel trowel and will remain workable for approximately 60 minutes after mixing.

STORAGE

Walkote must be stored in a cool dry place and free from moisture contact. **Walkote** has a shelf life of 12 months from the date of manufacture in unopened original container.

HEALTH AND SAFETY

Walkote is non-hazardous. In case of eye contact, wash with plenty of water. If irritation persists, seek immediate medical attention.

PACKAGING

Walkote is supplied in 25 kg bag.

The manufacturer reserves the right to change the specifications. Apurva India Limited products are guaranteed against material manufacture and are sold subject to the company's Terms and Conditions of Sale. Whilst we endeavour to ensure that advice, specifications, recommendations and information given is correct, we can not have control over how our products are applied and will not accept liability, directly or indirectly, arising from application of our materials.

Apurva's wide range of quality products meets the tough requirements of the building industry. Constant interaction with clients, regular improvisation to meet growing needs and a strong commitment to provide products that perform has made Apurva a truly trusted name in the field.

For further details please contact :

APURVA INDIA LIMITED

(FORMERLY APURVA BUILDCARE TECHNOLOGIES P LIMITED)

New Udyog Mandir No.2, 2nd Floor, Office No.2,
7C, Pitambar Lane, Mahim(w), Mumbai 400 016

Tel.No. 91 22 24475051/52/53/54/55, Fax No. 91 22 24475056

E.Mail: info@apurvaindia.in Website: www.apurvaindia.in

