



WALKOTE

SMOOTH SKIM RENDERING PASTE

PRODUCT DESCRIPTION

Walkote is a specially formulated **water resistant** polymer cement based putty suitable for plastered and concrete surfaces for both internal and external walls.

Walkote superior formulation is designed to provide a smooth durable finish with excellent adhesion strength. The surface can be either brushed or trowel finished to meet stringent requirements. Walkote yields a homogeneous paste that gives good workability on both vertical and overhead surfaces.

W

PRODUCT ADVANTAGES

- Premixed to ensure good consistent quality.
- Adjustable consistency & Excellent trowelability on application.
- Due to presence of cement and polymer, it provides a hard and tough surface.
- Being Cementitious it forms an excellent bond with plaster
- Seal all cracks and pores in the concrete
- Can be applied on moist plaster without waiting for drop in moisture. Hence improvement in Project Completion Schedule.
- Perfectly smooth finish.
- Compatible with decorative wall coatings.
- Water resistant and no curing required
- It prevents the growth of algae and fungi on walls.
- It is in dry powder form and does not produce any kind of unpleasant smell at the time of application.
- LEED compliance
- Ideal for use in Greenbuilding

PRODUCT SPECIFICATIONS

Method of Application:	Steel trowel/Putty blade
Drying Time:	
Surface Dry	3-4 hour
Hard dry	Overnight
No. of coats recommended:	2 coats
Coverage	: 1.5 kg/ m ² depending on porosity, roughness substrate conditions and also method of application.
Overcoating interval:	4 hours
Fungus Resistance:	Resistant to fungus growth
Colour Shade :	White
Surface finish:	Matt

METHOD OF APPLICATION

a) SURFACE PREPARATION

The surface must be clean, sound, dust-free, and without any traces of oil, laitance, paint or curing compound.

b) PRODUCT PREPARATION

Add approximately 9-10 litre of water to 25 kg of **Walkote**. Mix thoroughly for 3-5 minutes until the desired homogeneous paste is achieved.

c) PRODUCT APPLICATION

Walkote is applied using a steel trowel and will remain workable for approximately 60 minutes after mixing.

STORAGE

Walkote must be stored in a cool dry place and free from moisture contact. **Walkote** has a shelf life of 12 months from the date of manufacture in unopened original container.

HEALTH AND SAFETY

Walkote is non-hazardous. In case of eye contact, wash with plenty of water. If irritation persists, seek immediate medical attention.

SPECIAL INSTRUCTIONS

Stir the contents of the drum thoroughly to disperse the settled matter before use. Ensure that areas where coating work is being carried out are properly ventilated. It is advised that the workmen should use protectives like gloves, goggles etc.

PACKING

Walkote available in 25 kg packing size.

HANDLING & SAFETY

Keep the containers tightly sealed when not in use. Avoid skin contact and inhalation of fumes (if any). While spraying it is advised to wear a mask. If it comes in contact with the body, wash affected parts with plenty of water. In case of persistent irritation, contact a physician. It is advised that the workmen should use protective's like gloves, goggles etc

Disclaimer: The manufacturer reserves the right to change the specifications. Apurva India Limited products are guaranteed against material manufactured and are sold subject to the company's Terms and Conditions of Sale. Whilst we endeavour to ensure that advice, specifications, recommendations and information given is correct, we cannot have control over how our products are applied and will not accept liability, directly or indirectly, arising from application of our materials.

APURVA INDIA LIMITED

New Udyog Mandir No. 2, Office No. 2, 2nd floor, 7-C, Pitambar Lane, Mahim (W), Mumbai - 400 016, India.

Tel.: 91-22-24475051 | Fax: 91-22-24475056 | Website: www.apurvaindia.in

