

SEALCRETE

POLYMER MODIFIED CEMENTITIOUS WATERPROOFING COATING

PRODUCT DESCRIPTION

Two pack polymer cementitious coating system.

PURPOSE

Waterproofing of concrete surface and protection of concrete.

USAGE

Providing waterproof coating by application of brush or towel of the mixed material.

PRODUCT FEATURES

- Excellent water resistance.
- Excellent weatherability hence suitable for exterior application
- Being cementitious, it has similar expansion as concrete.
- Provides a tough, durable and flexible film and protects concrete from corrosive salts and atmosphere gases.
- Coating is breathable, allowing transmission of water vapour from interior of the building

APPLICATION AREAS

It is used to provide water and damp proofing coats to concrete structures, brick and masonry works, plasters etc. It is also used in underground retaining walls, tunnels and basements. Foundation walls and footing subjected to ground moisture can also be protected by coatings of SEALCRETE. It can also be used as a protective coat on CLEARSEAL roof waterproofing membrane.

PRODUCT CHARACTERISTICS

Pot Life at 30°C 20-25 min.
Application Temperature Not less than 10°C
Colours Available Grey and White
Coverage 1.5 kg. of mix per sq. mtr. per mm of thickness.

METHOD OF APPLICATION

1. **SURFACE PREPARATION** : Remove loose plaster, if any. All the cracks above 0.7 mm width should be properly sealed. The surface should be structurally sound and free from oil, grease and loose particles.
2. **FIRST COAT** : Take **FLEXCRETE** liquid and mix with water in ratio 1: 1 For each litre of mix add 2.5 kg or such quality of **SEALCRETE** powder slowly while stirring continuously either manually or mechanically till powder is dispersed into a homogeneous pasty brushable mass. Apply it over previously wetted and moist surface by means of stiff brush to get dry film thickness of 1 mm per coat.
3. **SECOND COAT** : After an interval of 3-4 hours apply second coat in a similar manner over the first one.

The manufacturer reserves the right to change the specifications. Apurva Buildcare Technologies P.. Limited products are guaranteed against material manufacture and are sold subject to company's Terms and Conditions of Sale. Whilst we endeavour to ensure that advice, specifications, recommendations and information given is correct, we cannot have control over how our products are applied and will not accept liability, directly or indirectly, arising from application of our materials.

Apurva's wide range of quality products meets the tough requirements of the building industry. Constant interaction with clients, regular improvisation to meet growing needs and a strong commitment to provide products that perform has made Apurva a truly trusted name in the field.

For further details please contact :

APURVA BUILD CARE TECHNOLOGIES P LIMITED

New Udyog Mandir No.2, 2nd Floor, Office No.2,
7C, Pitambar Lane, Mahim(w), Mumbai 400 016
Tel.No. 91 22 24475051/52/53/54/55, Fax No. 91 22 24475056
E.Mail: apurv@vsnl.com Website: www.apurvabuildcare.com

