



ELASTOCRETE

POLYMER MODIFIED CEMENTITIOUS ELASTOMERIC WATERPROOFING COATING

PRODUCT

Two pack polymer modified cementitious elastomeric coating system

PURPOSE

Waterproofing of concrete surface and protection of concrete.

USAGE

Providing waterproof coating by application of brush or trowel of the mixed material.

ADVANTAGES

- Forms highly flexible and elastomeric film.
- Excellent water resistance
- Excellent weatherability hence suitable for exterior application
- Excellent adhesion to concrete and other substrate
- Provides a tough, durable and flexible film and protects concrete from corrosive salts and atmosphere gases.
- Coating is breathable, allowing transmission of water vapour from interior of the building
- Nontoxic and easy to apply.
- Fills holes, cracks in concrete.
- Being flexible and elastomeric, it is specially suitable for surfaces which undergo movements

FIELDS OF APPLICATION

It is used to provide water and damp proofing coats to concrete structures, brick and masonry works, plasters, etc. It is also used in underground retaining walls, tunnels and basements. Foundation walls and footing subjected to ground moisture can also be protected by coatings of **ELASTOCRETE**.

TYPICAL APPLICATIONS

- Waterproof coatings for roofs
- Backing to marble, granite or other claddings to prevent water ingress
- Provide protection to concrete from carbonation and chloride attack
- Provide protection to foundations
- Car Park Decks
- Terrace gardens
- Swimming Pools
- Toilets and Bathrooms

P.T.O.

METHOD OF APPLICATION

SURFACE PREPARATION

Remove loose plaster, if any. All the cracks above 0.7mm width should be properly sealed. The surface should be structurally sound and free from oil, grease and loose particles.

FIRST COAT

Prepare the ELASTOCRETE mortar using ELASTOFLEX : Water : ELASTOCRETE in the ratio of 1:0.5:3. Mix the content slowly while continuous stirring manually or mechanically till powder is dispersed into a homogeneous pasty brushable mass. Apply it over previously wetted and moist surface by means of stiff brush to get dry film thickness of 1mm per coat. Add water if required so as to achieve brushability to the mixture.

TYPICAL PROPERTIES

Pot life at 30° C	-	20-25min.
Application Temp.	-	Not less than 10°C
Colours Available	-	Grey and White
Coverage	-	Spread 1.5kg. of mix per sq.mt/mm

The manufacturer reserves the right to change the specifications. Apurva India Limited products are guaranteed against material manufacture and are sold subject to the company's Terms and Conditions of Sale. Whilst we endeavour to ensure that advice, specifications, recommendations and information given is correct, we can not have control over how our products are applied and will not accept liability, directly or indirectly, arising from application of our materials.

Apurva's wide range of quality products meets the tough requirements of the building industry. Constant interaction with clients, regular improvisation to meet growing needs and a strong commitment to provide products that perform has made Apurva a truly trusted name in the field.

For further details please contact :

Apurva India Limited

{Formerly Apurva Buildcare Technologies Pvt Ltd}

New Udyog Mandir No2, 2nd floor, Office No: 2

7-C, Pitamber Lane, Mahim-West

MUMBAI- 400 016

INDIA

Tel. +91 22 2447 5051

Fax +91 22 2447 5056

Email : info@apurvaindia.in Website : www.apurvaindia.in

