



DURASHIELD SB

WEATHERPROOF SOLVENT BASED TRANSPERENT COATING FOR BUILDINGS FACADES

PRODUCT DESCRIPTION

High performance polymer based weatherproofing coating to provide wet look to stones on building exteriors. It offers long term protection, retention of good aesthetics, excellent UV and fungus resistance.

PRODUCT ADVANTAGES

- It forms a smooth and durable film
- Fungus Control - Due to incorporation of highly effective broad spectrum of fungicide, it offers long term protection against fungal growth.
- UV Resistance - It is completely resistant to UV radiation.
- No chalking and peeling.

APPLICATION AREAS

Excellent composition for exterior wall coatings.

PRODUCT SPECIFICATIONS

| | |
|---------------------------|--|
| Method of Application: | Brush/Roller/Spray |
| Drying Time: | |
| Surface Dry | 25-30 minutes |
| Hard dry | 2-3 hours |
| Recoating Interval: | 4 hours minimum |
| No. of coats recommended: | 2 coats |
| Coverage | : 5 to 6 m ² /kg for 2 coats depending on surface porosity and roughness over the primed surface. |
| Fungus Resistance: | Resistant to fungus growth |
| Surface Finish | : Smooth sheen |
| Packing size | 18kgs, 10 kgs, 5 kgs |

SURFACE PREPARATION

The concrete or plastered surface should be washed and cleaned to remove dust, dirt, old paint, if any and laitance. The surface should be minimum 28 days old. All column or beam and wall joints should be checked thoroughly and sealed. All cracks above 1mm width should be properly sealed with non shrink grouts or sealants. The surface should be free of any oil and grease.

TOP COAT

Apply two or more coats of **DURASHIELD-SB** on a properly prepared surface with an intercoat interval 4 hours.

SHELF LIFE

DURASHIELD-SB has a shelf life of 6 months if kept in warehouse conditions at 30°C in the original, unopened pack.

STORAGE CONDITIONS

Store in dry conditions between 5°C and 30°C, away from sources of heat and naked flames, in the original, unopened packs. If stored at high temperatures the shelf life will be reduced.

SPECIAL INSTRUCTIONS

- Stir the contents of the drum thoroughly to disperse the settled matter.
- Do not store the drums in direct sunlight.

HANDLING & SAFETY

Keep the containers tightly sealed when not in use. Avoid skin contact and inhalation of fumes (if any). While spraying it is advised to wear a mask. If it comes in contact with the body, wash affected parts with plenty of water. In case of persistent irritation, contact a physician. It is advised that the workmen should use protectives like gloves, goggles etc

Disclaimer: The manufacturer reserves the right to change the specifications. Apurva India Limited products are guaranteed against material manufactured and are sold subject to the company's Terms and Conditions of Sale. Whilst we endeavour to ensure that advice, specifications, recommendations and information given is correct, we cannot have control over how our products are applied and will not accept liability, directly or indirectly, arising from application of our materials.

APURVA INDIA LIMITED

New Udyog Mandir No. 2, Office No. 2, 2nd floor, 7-C, Pitambar Lane, Mahim (W), Mumbai - 400 016, India.

Tel.: 91-22-24475051 | Fax: 91-22-24475056 | Website: www.apurvaindia.in

