



DURASHIELD-SB

WEATHERPROOF SOLVENT BASED TRANSPERENT COATING FOR BUILDINGS FACADES

PRODUCT DESCRIPTION

High performance polymer based weatherproofing coating to provide wet look to stones on building exteriors. It offers long term protection, retention of good aesthetics and retaining stone cast due to excellent UV and fungus resistance.

PRODUCT ATTRIBUTES

- It forms a smooth and durable film
- Fungus Control - Due to incorporation of highly effective broad spectrum fungicide, it offers long term protection against fungal growth.
- UV Resistance - It is completely resistant to UV radiation.
- No chalking and peeling.

PRODUCT SPECIFICATIONS

| | |
|----------------------------|--|
| Form..... | Pasty liquid |
| Method of Application..... | Brush, roller or Spray |
| Drying Time..... | 30 minutes (surface dry) 2 hours (hard dry) (Depends on Relative Humidity and Temperature) |
| Recoating Interval..... | 4 hours (minimum) |
| Number of Coats..... | 2 coats (minimum) |
| Recommended | |
| Covering Capacity..... | 5 to 6 m ² /kg for 2 coats depending on surface porosity and roughness. |
| Fungus Resistance..... | Resistant to fungus |
| Shelf Life..... | Minimum 6 months if sealed drum is not opened |

METHOD OF APPLICATION

a) SURFACE PREPARATION

The surface should be washed and cleaned to remove dust, dirt, if any and laitence. All stone joints should be properly sealed with non shrink grouts or suitable sealents. The surface should be free of any oil and grease.

b) TOP COATS

Apply two or more coats of **DURASHIELD-SB** on a properly prepared surface with an intercoat interval of 4 hours.

SPECIAL INSTRUCTIONS

- Stir the contents of the drum thoroughly to disperse the settled matter.
- Do not store the drums in direct sunlight.

The manufacturer reserves the right to change the specifications Apurva India Limited products are guaranteed against material manufacture and are sold subject to the company's Terms and Conditions of Sale. Whilst we endeavour to ensure that advice, specifications, recommendations and information given is correct, we can not have control over how our products are applied and will not accept liability, directly or indirectly, arising from application of our materials.

Apurva's wide range of quality products meets the tough requirements of the building industry. Constant interaction with clients, regular improvisation to meet growing needs and a strong commitment to provide products that perform has made Apurva a truly trusted name in the field.

For further details please contact :

APURVA INDIA LIMITED

(FORMERLY APURVA BUILD CARE TECHNOLOGIES P LIMITED)

New Udyog Mandir No.2, 2nd Floor, Office No.2,
7C, Pitambar Lane, Mahim(w), Mumbai 400 016
Tel.No. 91 22 24475051/52/53/54/55, Fax No. 91 22 24475056
E.Mail: info@apurvaindia.in Website: www.apurvaindia.in


