



DURASHIELD WB

TRANSPARENT SEALER COATING FOR BUILDING FACADES

PRODUCT DESCRIPTION

High performance acrylic latex based weatherproofing sealer coating for maintaining natural look of stones on building exteriors. It offers long term protection, retention of good aesthetics ,excellent UV and fungus resistance.

PRODUCT ADVANTAGES

- Seals the pores and forms a smooth film
- Fungus Control - Due to incorporation of highly effective broad spectrum fungicide, it offers long term protection against fungal growth.
- UV Resistance - It is completely resistant to UV radiation.
- Excellent Breathability - Coating is permeable to water vapour.
- No chalking and peeling.

APPLICATION AREAS

Excellent composition for exterior wall coatings.

PRODUCT SPECIFICATIONS

Method of Application:	Brush/Roller/Spray
Drying Time:	
Surface Dry	25-30 minutes
Hard dry	2-3 hours
Recoating Interval:	4 hours minimum
Coverage	: 6 to 8 m ² /kg for 2 coats depending on surface porosity and roughness
Fungus Resistance:	Resistant to fungus growth
Packing size	30kgs,20 kgs, 5 kgs

SURFACE PREPARATION

The concrete or plastered surface should be washed and cleaned to remove dust, dirt, old paint, if any and laitance. The surface should be minimum 28 days old. All column or beam and wall joints should be checked thoroughly and sealed. All cracks above 1mm width should be properly sealed with non shrink grouts or sealants. The surface should be free of any oil and grease.

TOP COAT

Apply **DURASHIELD-WB** on a properly prepared surface for sealing the pores. If a thicker film is desired more coats may be applied.

SHELF LIFE

DURASHIELD-WB has a shelf life of 6 months if kept in warehouse conditions at 30°C in the original, unopened pack.

STORAGE CONDITIONS

Store in dry conditions between 5°C and 30°C, away from sources of heat and naked flames, in the original, unopened packs. If stored at high temperatures the shelf life will be reduced.

SPECIAL INSTRUCTIONS

- Stir the contents of the drum thoroughly to disperse the settled matter.
- Do not store the drums in direct sunlight.

HANDLING & SAFETY

Keep the containers tightly sealed when not in use. Avoid skin contact and inhalation of fumes (if any). While spraying it is advised to wear a mask. If it comes in contact with the body, wash affected parts with plenty of water. In case of persistent irritation, contact a physician. It is advised that the workmen should use protectives like gloves, goggles etc

Disclaimer: The manufacturer reserves the right to change the specifications. Apurva India Limited products are guaranteed against material manufactured and are sold subject to the company's Terms and Conditions of Sale. Whilst we endeavour to ensure that advice, specifications, recommendations and information given is correct, we cannot have control over how our products are applied and will not accept liability, directly or indirectly, arising from application of our materials.

APURVA INDIA LIMITED

New Udyog Mandir No. 2, Office No. 2, 2nd floor, 7-C, Pitambar Lane, Mahim (W), Mumbai - 400 016, India.

Tel.: 91-22-24475051 | Fax: 91-22-24475056 | Website: www.apurvaindia.in

