

DURASHIELD-WB

TRANSPARENT SEALER COATING FOR BUILDINGS FACADES

PRODUCT DESCRIPTION

High performance acrylic latex based weatherproofing sealer coating for maintaining natural look of stones on building exteriors. It offers long term protection, retention of good aesthetics and retaining stone cast due to excellent UV and fungus resistance.

PRODUCT ATTRIBUTES

- Seals the pores and forms a smooth film
- Fungus Control - Due to incorporation of highly effective broad spectrum fungicide, it offers long term protection against fungal growth.
- UV Resistance - It is completely resistant to UV radiation.
- Excellent Breathability - Coating is permeable to water vapour.
- No chalking and peeling.

PRODUCT SPECIFICATIONS

Form.....	Liquid
Method of Application.....	Brush, roller or Spray
Drying Time.....	30 minutes (surface dry) 2 hours (hard dry) (Depends on Relative Humidity and Temperature)
Recoating Interval.....	4 hours (minimum)
Covering Capacity.....	6-8 m ² /kg depending on surface porosity and roughness.
Fungus Resistance.....	Resistant to fungus
Shelf Life.....	Minimum 6 months if sealed drum is not opened

METHOD OF APPLICATION

1. SURFACE PREPARATION

The surface should be washed and cleaned to remove dust, dirt, if any and laitence. All stone joints should be properly sealed with non shrink grouts or suitable sealents. The surface should be free of any oil and grease .

2. TOP COATS

Apply one coat of **DURASHIELD-WB** on a properly prepared surface for sealing the pores. If a thicker film is desired more coats may be applied.

SPECIAL INSTRUCTIONS

- * Stir the contents of the drum thoroughly to disperse the settled matter.
- * Do not store the drums in direct sunlight.

The manufacturer reserves the right to change the specifications. Apurva Buildcare Technologies P. Limited products are guaranteed against material manufacture and are sold subject to the company's Terms and Conditions of Sale. Whilst we endeavour to ensure that advice, specifications, recommendations and information given is correct, we can not have control over how our products are applied and will not accept liability, directly or indirectly, arising from application of our materials.

Apurva's wide range of quality products meets the tough requirements of the building industry. Constant interaction with clients, regular improvisation to meet growing needs and a strong commitment to provide products that perform has made Apurva a truly trusted name in the field.

For further details please contact:

APURVA BUILD CARE TECHNOLOGIES P LIMITED

New Udyog Mandir No.2, 2nd Floor, Office No.2,

7C, Pitambar Lane, Mahim(w), Mumbai 400 016

Tel.No. 91 22 24475051 to 24475055, Fax No. 91 22 24475056

E.Mail: apurv@vsnl.com Website: www.apurvabuildcare.com

