

POLYDECK-FC

POLYURETHANE BASED FINISH COAT FOR CAR PARK DECKS

PRODUCT DESCRIPTION

POLYDECK-FC is a solvent based two components, based on polyurethane resin. **POLYDECK-FC** combines superior chemical and abrasion resistance with excellent adhesion, colour retention and weatherability.

PRODUCT ADVANTAGES

- Long term colour retention and excellent U.V resistance
- Seamless and hygienic finish, no crevices where dirt and bacteria can dwell.
- Easy cleaning and low maintenance.
- Protects against moisture penetration.
- Exceptional resistance to chemicals and cleaning solvents.
- Non-Slip finish can be tailored to requirements.
- Flexible, can be used over wood and steel

TYPICAL USES, ADVANTAGES

POLYDECK-FC is a general service polyurethane coating designed to improve cleanability, increase stain resistance and abrasion resistance.

- High Build finish course for Car Parks
- Packaging areas.
- Warehousing areas.

PHYSICAL CHARACTERISTICS

Application.....	Brush, Roller.
Mixing ratio.....	Base: Hardener 100:15 or as directed on the container.
Pot Life.....	60 Minutes.at 23°C
Drying Time.....	Touch Dry-30 Mins, Hard Dry-6 Hrs.
Intercoat Interval.....	6-8 Hours Minimum.
Dry Film Thickn.....	70-100 microns/kg per coat depending on porosity.
Coverage.....	5-7 sq.mts/kg per coat depending on porosity, roughness &method of application.
Recommended no. of coats.....	2 min.

METHOD OF APPLICATION

APURVA's system should be installed by approved contractors. Following information should be used as a guideline.

1. MIXING

Pack components are pre-weighed for optimum performance. Never split packs. Empty contents of component B into a mixing container and pre-mix to assure the suspension of solids. Add component A and continue to mix to a uniform consistency for 1-2 minutes. Mix with slow speed drill and helical spinner head for 2 minutes. Avoid high speed mixing that will entrain air into the mix.

2. APPLICATION

POLYDECK-FC must be applied immediately after mixing the two components. **POLYDECK-FC** is applied with a rubber squeegee and medium nap roller. The roller is used to remove squeegee lines and smooth out the surfaces. Each additional coat may be applied when surface is tack free, which is about 6 hours.

..2/-

APURVA INDIA LIMITED

New Udyog Mandir No. 2, Office No. 2, 2nd floor, 7-C, Pitambar Lane, Mahim (W), Mumbai - 400 016, India.

Tel.: 91-22-24475051 | Fax: 91-22-24475056 | Website: www.apurvaindia.in



3. CURING

The surface of **POLYDECK-FC** will be tack free in 6-8 hours. The coated area may be put back in service 2 days.

SPECIAL CONDITIONS

Colours

We shall always endeavour to supply the material in the colour shade ordered. However exact matching will not be possible.

Batch to batch colour variation may occur. Ensure that materials for final application are always drawn from the same batch.

Where colour matching is required over more than one order or delivery. Apurva's Technical department must be contacted prior to placing the order(s) a requirement stated clearly on all orders relating to the project(s).

RECOMMENDATIONS

Apply only on a clean sound and properly prepared substrate.

Do not use water or steam in the vicinity of the application. Moisture can seriously affect the working time and properties of material.

STORAGE CONDITIONS

Store all components of **POLYDECK-FC** unopened in shade. Avoid excessive heat. The shelf life is 1 year in original, unopened container.

PACKAGING

POLYDECK-FC is packaged in packs for easy handling. Each pack consists of
3 Kg of Curing Agent (Component A)
20 Kg of Base (Component B)

HANDLING AND SAFETY

Keep the containers tightly sealed when not in use. Avoid skin contact and inhalation of fumes (if any). While spraying it is advised to wear a mask. If it comes in contact with the body, wash affected parts of plenty of water. In case of persistent irritation, contact a physician.

The manufacturer reserves the right to change the specifications. Apurva India Limited products are guaranteed against material manufacture and are sold subject to the company's Terms and Conditions of Sale. Whilst we endeavour to ensure that advice, specifications, recommendations and information given is correct, we can not have control over how our products are applied and will not accept liability, directly or indirectly, arising from application of our materials.

Apurva's wide range of quality products meets the tough requirements of the building industry. Constant interaction with clients, regular improvisation to meet growing needs and a strong commitment to provide products that perform has made Apurva a truly trusted name in the field.