

# WALGARD

## HYGIENIC INTERIOR WALL FINISH

### Product Description

One pack solvent borne interior wall finish designed to provide rich, lustrous, very smooth and hard film with antifungal properties. Due to the extra ordinary adhesion, it can be applied on various substrates like Concrete, Plaster of Paris, Steel, Wood, Plastics etc.

### Features

- It forms a very smooth and hard film.
- Fungus and Bacteria Control - Due to incorporation of broad spectrum of fungicide it does not allow any fungal growth.
- Very high stain resistance.
- Unmatched rich and lustrous finish.
- Easy to clean
- Good resistance to water and cleaning chemicals. Frequent cleaning is possible.

### Uses

- Sterile and clean rooms in pharmaceutical industry.
- Electronics assembly and Computer Rooms.
- Hospitals
- Hotels and Flight Kitchens.
- Dairies and Breweries.
- Food and Meat Processing Plants.
- Residential Premises

### Properties

Method of Application: Brush/Roller/Spray

Surface Finish: Matt, Semi Matt

Drying Time:

Surface Dry 30-45 hour

Hard dry 4-6 hours

No. of coats recommended: 2 coats

Coverage : 9-10 m<sup>2</sup> / kg per coat depending on porosity, roughness substrate conditions and also method of application.

Fungus Resistance: Resistant to fungus growth

Colour Shades : White, grey and pastel shades

Packing : 5, 20 kg

### Surface Preparation

Surfaces should be free of defects and contamination. All contaminants such as dirt, oils, wax and medium to heavy chalk must be removed to ensure proper adhesion to the substrate. Chipping or peeling paint must be removed prior to application of WALGARD.

### Method of Application

**WALGARD** should be applied on properly levelled and smoothed substrate using Brush or Roller. Apply 2 or 3 coats till proper finish is achieved.

### Shelf Life

**WALGARD** has a shelf life of 6 months if kept in warehouse conditions at 30°C in the original, unopened pack.

### Storage Conditions

Store in dry conditions between 5°C and 30°C, away from sources of heat and naked flames, in the original, unopened packs. If stored at high temperatures the shelf life will be reduced.

### Special Instructions

Stir the contents of the drum thoroughly to disperse the settled matter before use.

Ensure that areas where coating work is being carried out are properly ventilated.

It is advised that the workmen should use protective like gloves, goggles etc..

### Handling & Safety

**Keep the containers tightly sealed when not in use. Avoid skin contact and inhalation of fumes (if any). While spraying it is advised to wear a mask. If it comes in contact with the body, wash affected parts with plenty of water. In case of persistent irritation, contact a physician.**

**It is advised that the workmen should use protectives like gloves, goggles etc**

**Disclaimer:** *The manufacturer reserves the right to change the specifications. Apurva India Private Limited products are guaranteed against material manufactured and are sold subject to the company's Terms and Conditions of Sale. Whilst we endeavour to ensure that advice, specifications, recommendations and information given is correct, we cannot have control over how our products are applied and will not accept liability, directly or indirectly, arising from application of our materials.*

*Version No.04/Date of revision : July 2017*

**APURVA INDIA PRIVATE LIMITED**

New Udyog Mandir No. 2, Office No. 2, 2nd Floor, 7C Pitambar Lane, Mahim (W), Mumbai 400 016, India.  
Tel: +91-22-24475051 (5 Lines) | Fax: +91-22-24475056 | Website: [www.apurvaindia.in](http://www.apurvaindia.in)

